		5% on 3 compress		
If your compressor works more than Our technicians are at your disposal	30 minutes per hour it means that it is too small. Please remember to drain for any further information. All of our compressors are in accordance with	n the condensate at least one EEC regulations.	ce a wee	ek.
ILLUSTRATION	DESCRIPTION	Suitable for:	Price	Co
	Silent Compressor HP 1/2 - 50/24 - Air intake: 50 lt/min - 24 liters tank - Watt 340 - Volt 220 - singlephase motor HP 0.5 - Maximum pressure 8 atm - Safety valve, pressure reducer - Manometer for pressure control with filter and 2 air exhausts - Automatic safe-engine - Noise: 40 decibel - Size: 400x400x600 mm - Net Weight 24 Kg - Gross 26 Kg	Suitable for: 1 underpinner or 3-4 air guns	530	343
	Silent Compressor 2 motors HP 1 - 100/24 - Air intake: 100 lt/min - 24 liters tank - Watt 680 - Volt 220 - 2 singlephase motors HP 1 - Maximum pressure 8 atm - Automatic electric pressure switch, safety valve - Manometer for pressure control with filter and 2 air exhausts - Automatic safe-engine - Noise: 47 decibel - Size: 330x700x540 mm - Net Weight 39 Kg - Gross 42 Kg	Suitable for: 1 underpinner or 1 pneumatic guillotine or 4-5 air guns	830	343
	Silent Compressor 2 motors HP1 - 100/50 - Air intake: 100 lt/min - 50 liters tank - Watt 680 - Volt 220 - 2 singlephase motors HP 1 - Maximum pressure 8 atm - Automatic electric pressure switch, safety valve - Manometer for pressure control with filter and 2 air exhausts - Automatic safe-engine - Noise: 47 decibel - Size: 330x1050x570 mm Net Weight 50 Kg - Gross 57 Kg	Suitable for: 1 underpinner or 1 pneumatic guillotine or 5-6 air guns	970	34:
	Silent Compressor SIL-AIR 150/50 by Werther - Air intake: 150 lt/min 50 liters tank - Watt: 1020 - Volt: 230 - 3 Singlephase motor HP 1 - Maximum pressure: 8 atm. - Manometer for pressure control - 2 Air exhausts - Pressure reducer - Safety valve - Automatic safe-engine - Noise: 49 decibel - Size: cm 40x86x75 - Net Weight 75 Kg - Gross 83 Kg	Suitable for: 2 underpinners or 1 pneumatic guillotine or 1 double mitre saw or 5/6 air guns	1.280	34
	Silent Compressor SIL-AIR 200/10 by Werther - Air intake: 200 It/min 100 liters tank - Watt: 1360 - Volt: 220 - 4 Singlephase motor HP 1 - Maximum pressure: 8 atm. - Manometer for pressure control - 2 Air exhausts - Pressure reducer - Safety valve - Automatic safe-engine - Noise: 49 decibel - Size: cm 40x127x65 - Net Weight 95 Kg - Gross 100 Kg	Suitable for: 2 underpinners or 1 pneumatic guillotine or 1 double mitre saw or 6/7 air guns	1.820	34

ACCESSORIES FOR COMPRESSORS

Westerfler	Description			Price Discount Q.ty %		- Code		Description		Price	Discount		
Illustration			Price				Illustration				Q.ty	%	Code
	The filter is used to filter the condensate from the compressors		23,00	3	6%	3471		Y-shaped diverter used t compressed air into two		2,90	3	10%	3483
Ta 🛄 🛄	The lubricator is used to keep the		30,00	3	6%	3472		Bayonet head,	male	1,80	3	10%	3484
	tubes lubricated			Ŭ	0 /0			threaded	female	2,60	3	10%	3484F
	Filter regulator used to regulate air pressure		39,00	3	6%	3473		T-fitting for bayonet connection or threaded connection		5,00	3	10%	3485
Manometer used to show the degree of air pressure		w the	6,90	3	10%	3475		Line cock, male-female		6,20	3	10%	3486
	Pressure regulator without filter Internal diameter 6 mm		26,00	3	6%	3475R		Tape in teflon to seal tri mm 12x10 metres	mmings.	1,20	3	10%	348T
	Quick exhaust with spring, Italian profile. Internal diameter 6 mm		9,00	3	10%	3476		Oil for silent compressor.		11,50	3	6%	343L
	Quick coupling with spring, Italian profile. Internal diameter 6 mm		2,20	3	10%	3477		Fluid for nebulizers		10,50	3	6%	3487
FE EDMANNA	Bayonet-shaped connection with spring		2,30	3	10%	3478		Coil nose, without connections 30 metrers long		46,00	3	6%	349
	Quick coupling, Italian profile, threaded		1,30	3	10%	3479	Contraction of	Coil nose,	5 mt long	11,00	3	6%	348R5
		female	1,20	3	10%	3479F	4	with bayonet joint and connection	12 mt long	14,00	3	6%	348R12
	Fitting with nut for m						External diam: 8 mm	Tube for compressed air.	10 mt pack	13,50	3	10%	3488D
		male	1,90	3	10%	3480		External diam: 8 mm Internal diam: 6 mm	50 mt pack	52,00	3	10%	3488F
	Dayoner connection	female	1,80	3	10%	3481			100 mt pack	97,00			3488C